

$\text{D} \cdot \text{D}^2 \tilde{\text{N}} \cdot \text{D}^{3/4} \text{D} \cdot \text{D}^\circ \text{D} ; \tilde{\text{N}} \text{D}^\circ \tilde{\text{N}} \cdot \tilde{\text{N}} \text{D}$
 $\text{D} \cdot \text{D} \gg \tilde{\text{N}} \cdot \text{D} \cdot \text{D}^{1/2} \text{D}^{3/4} \text{D}^{1/4} \text{D}^\circ \tilde{\text{N}} \in \text{D}^{3/4} \text{D}^\circ \text{D}^3.$
 $\text{D} \text{š} \text{D} , \text{D}^{1/2} \text{D}^3 \text{D} , \tilde{\text{N}} \cdot \text{D} \mu \text{D} ; \text{D} ;$

ĐŽĐŽĐŽ Đ•Đ^{1/2}Ñ,Đ°Đ»

ĐœĐ°Ñ•Đ»Đ^{3/4} Đ^{1/4}Đ^{3/4}Ñ,Đ^{3/4}Ñ∈Đ^{1/2}Đ^{3/4}Đμ
HC-Ñ•Đ,Đ^{1/2}Ñ,ĐμÑ,Đ,Ñ‡ĐμÑ•Đ°Đ^{3/4}Đμ LIQUI MOLY
Top Tec 4600 5W30 API SN, ACEA C2/C3

ÑfĐ± 1 410.00



[Đ^{1/2}Ñ,Đ^{3/4}Ñ∈Đ^{1/4}Đ°Ñ‡Đ,Ñ•Đ^{3/4}Đ;Ñ∈Đ^{3/4}Đ°Đ²Ñ‡Đμ](#)

ĐœĐ^{1/2}ĐμĐ^{1/2}Đ,Ñ•Đ;Đ^{3/4}Đ°ÑfĐ;Đ°Ñ,ĐμĐ»ĐμĐ¹: Đ•Ñ%Đμ Đ^{1/2}ĐμÑ, Đ^{1/4}Đ^{1/2}ĐμĐ^{1/2}Đ,Đ¹Đ^{3/4}Đ±Ñ•Ñ,Đ^{3/4}Đ^{1/4}Ñ,Đ^{3/4}Đ²Đ°Ñ∈Đμ.

ĐŸĐ^{3/4}Đ¶Đ°Đ»ÑfĐ¹Ñ•Ñ,Đ°,Đ²Đ^{3/4}Đ¹Đ°Đ,Ñ,Đμ,Ñ‡Ñ,Đ^{3/4}Đ±Ñ<Đ^{3/4}Ñ•Ñ,Đ°Đ²Đ,Ñ,ÑœÑ•Đ²Đ^{3/4}ĐμĐ^{1/4}Đ^{1/2}ĐμĐ^{1/2}Đ,Đμ.